

The Reliable Supplier for Power System Solution

RICARDO 35-90 kVA



Easy maintenance canopy design



Refilling from the outside of the canopy



Warning system for decreasing fuel with electronic fuel level sender

Technical Specifications

ENGINE

- RICARDO series heavy duty diesel engine
- 4 cycle, water cooled, natural / turbocharged / turbocharged and air to air charge cooled
- Direct injection
- Electronic governor system
- 12/24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with CE, ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)

- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION AND ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure

Ricardo Series Diesel Generator Sets 35-90 kVA

MODEL		SPRC35	SPRC55	SPRC75	SPRC90
ENGINE					
BRAND		RICARDO	RICARDO	RICARDO	RICARDO
TYPE		K4100D	K4100ZD	R4105ZD	4105IZLD
POWER (kW)	STAND BY	30	42	61	73
	PRIME	28	38	56	65
SPEED (rpm)		1500	1500	1500	1500
CYCLE		4	4	4	4
DISPLACEMENT (l)		4,21	4,21	4,33	4,75
NUMBER OF CYLINDERS / ALIGNMENT		4 IN LINE	4 IN LINE	4 IN LINE	4 IN LINE
BORE AND STROKE (mm / mm)		100 / 115	100 / 115	100 / 125	105 / 130
COMPRESSION RATIO		19:1	17:1	17:1	17:1
GOVERNOR TYPE		ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC
INDUCTION		NATURAL	TURBOCHARGED	TURBOCHARGED	TURBOCHARGED & AIR TO AIR CHARGE COOLED
COOLING SYSTEM		WATER	WATER	WATER	WATER
FUEL CONSUMPTION (l/h)	100% OF PRIME POWER	10	11	15	15
	75% OF PRIME POWER	7,5	8,25	11,25	11,25
	50% OF PRIME POWER	5	5,5	7,5	7,5
	25% OF PRIME POWER	2,5	2,75	3,75	3,75
FUEL TANK CAPACITY (l)		100	110	150	150
GROUP					
GEN - SET POWER	STAND BY	35 kVA / 28 kW	55 kVA / 44 kW	75 kVA / 60 kW	90 kVA / 72 kW
	PRIME	32 kVA / 26 kW	50 kVA / 40 kW	68 kVA / 54 kW	81 kVA / 64 kW
CANOPY DIMENSION (W x L x H) (mm)		1100 x 2300 x 1700	1100 x 2300 x 1700	1100 x 2300 x 1700	1100 x 2300 x 1700
CANOPY WEIGHT (kg)		800	1200	1300	1400

Samurai Power reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.