



USB
plug



Plug & Play
installation



SOHO

The AiO All-in-One UPS series, featured with smart microprocessor control design, AVR boost and Buck, Smart USB communication interface and cold start function, is an ideal solution for protecting household and small office systems. In addition, the UPS is built-in USB charger, which may charge your mobile, PAD, etc. alone.


Features :

- Boost and Buck AVR corrects either under-voltage or over-voltage condition to minimize the usage of battery energy, hence to extend the life of the battery.
- Built-in USB charger supplies feasible access to recharge your mobile or PAD alone.
- With ergonomic cable management design, all the access of the cables is from top only.
- Cold Start Function aids users to turn on the UPS without connecting the Utility.
- Smart USB Interface for Power Management supports real-time power and UPS status monitoring. Automatic shutdown, schedule and many other advance power management functions.
- Auto-restart Function enables the UPS may be automatically re-started when Utility recovers.

AiO All-in-One Line-interactive UPS

AiO 600 | AiO 800

AiO All-in-One Line-interactive UPS

MODEL	AiO 600		AiO 800	
CAPACITY	600VA / 360W		800VA / 480W	
INPUT				
Voltage	110/120 VAC or 220/230/240 VAC			
Voltage Range	81~145Vac or 162~290Vac			
Frequency Range	50/60Hz+/-10% auto-sensing			
OUTPUT				
Voltage Regulation	±10% for both AC mode and Battery mode			
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz			
Transfer Time	Typical 2-6 ms, 10ms max.			
Waveform (Batt. Mode)	Simulated Sine Wave			
BATTERY				
Battery Type & Number	12V/7AH x 1		12V/9AH x 1	
Typical Recharge Time	6-8 hours recover to 90% capacity			
INDICATORS				
AC Mode	Green LED lighting			
Battery Mode	Amber LED flashing			
Fault	Red LED lighting			
PROTECTION				
Full Protection	Overload and overcharge protection			
ALARM				
Battery Mode	Sounding every 10 seconds			
Low Battery	Sounding every second			
Overload	Sounding every 0.5 second			
Battery Replacement Alarm	Sounding every 2 seconds			
Fault	Continuously sounding			
PHYSICAL				
Dimension(D*W*Hmm)	270 x 190 x 90			
Details				
Net Weight (kgs)	3.55		4.9	
OPERATING ENVIRONMENT				
Humidity	0-90 % RH @ 0- 40°C (non-condensing)			
Noise Level	Less than 40dB			
MANAGEMENT				
Optional USB Port	Supports Windows® , Linux, Unix, and MAC			
USB CHARGER	for mobile & PAD charging			



Specifications subject to change without prior notice.

